

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance **Product Name: UltraLube LMX® "Red" Grease**
Part Numbers: 10320

Use of the Substance Shortened Product name: UL Grease LMX Red

CAS No. Mixture

Supplier Plews Edelman
1550 Franklin Grove Rd. Dixon, IL 61021

Manufacturer Address Environmental Lubricants Manufacturing, Inc.
311 B Ave -Grundy Center, IA 50638

SDS Questions: (800) 323-6294

Emergency telephone: CHEMTREC: (800) 824-9300

2. HAZARDS IDENTIFICATION

This preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Physical hazards Not classified as a physical hazard.

Health hazards Not Classified as a health hazard.

Environmental hazards Not classified as an environmental hazard.

Specific hazards May form vapors or oil mists during mechanical action or at elevated temperatures which may be irritating to the respiratory tract. Excessive inhalation of oil mist may affect respiratory system. Dermatitis after prolonged exposure. Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema/chapping and oil acne.

Main symptoms Irritant effects. Irritation of eyes and mucous membranes.

Label Elements Label in accordance with (EC) no. 1272/2008 No pictogram required

Other Hazards Not classified as PBT/vPvB by current EU criteria

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	% Weight
Vegetable Oil	68956-68-3	[70-95%]

4. FIRST-AID MEASURES

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if irritation develops or persists.
Ingestion	Drink 1 or 2 glasses of water. Get medical attention if any discomfort continues.
Most important symptoms and	
Effects	Symptoms include itching, burning, redness, and tearing of eyes.
General advice	Get medical attention if any discomfort develops.
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Dry chemical, foam, carbon dioxide.
Extinguishing media which must not be used for safety reasons	Do not use water jet as an extinguisher, as this will spread the fire.
Unusual fire & explosion Hazards	None known
Specific hazards	Thermal decomposition may produce smoke, oxides of carbon and lower molecular weight organic compounds whose composition have not been characterized.
Special protective equipment for fire-fighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk. Use water spray to cool unopened containers. Cool containers with flooding quantities of water until well after fire is out.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	When working with heated grease, mechanical ventilation may be required. Remove sources of ignition. Avoid contact with skin and eyes. For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.
Environmental precautions	Do not allow to enter drains, sewers or watercourses. Collect and dispose of spillage as indicated in Section 13. Contact local authorities in case of spillage to drain/aquatic environment.
Methods for cleaning up	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Small Spills: Absorb spillage with oil-absorbing material.

Large Spills: Absorb spilled substance with sand or earth.

7. HANDLING AND STORAGE

Handling	Handle and open container with care. Wear appropriate personal protective equipment. Avoid prolonged and repeated contact with grease, particularly used grease. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Use work methods which minimize production of vapors and mists. Observe good industrial hygiene practices.
Storage	Keep away from heat, sparks and open flame. Store in a cool and well-ventilated place. Store away from incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits	No exposure limits noted for ingredient(s).
Exposure controls	Provide adequate ventilation. When working with heated oil, mechanical ventilation may be required. Provide access to washing facilities including soap, skin cleanser and fatty cream.
Respiratory protection	In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter (type P2). Seek advice from local supervisor.
Hand protection	Wear protective gloves. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.
Eye protection	If risk of splashing, wear safety goggles or face shield.
Skin and body protection	Wear suitable protective clothing. Frequent change of gloves is advisable.
General	Use personal protective equipment as required. Personal protective equipment should be chosen-

Boiling point	Not available
Flash point	NA
Flammability	Not available
Flammability limits in air, upper, % by volume	Not available
Flammability limits in air, lower, % by volume	Not available
Vapour pressure	< 0.5 mm Hg at 20 °C
Relative density	0.92
Solubility (water)	Practically insoluble
Partition coefficient (n-octanol/water)	Not available
Viscosity	Not available
Vapour density	> 1 (Air = 1)
Evaporation rate	< 1 (n-Butylacetate = 1)
Melting point	Not available
Freezing point	Not available
Auto-ignition temperature	Not available
VOC	0 %

10. STABILITY AND REACTIVITY

Stability	Stable at normal conditions.
Conditions to avoid	High temperatures, Exposure to light, Contact with incompatible materials.
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition Products	At thermal decomposition temperatures, carbon monoxide and carbon dioxide. Nitrogen oxides.
Hazardous polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	May form vapors or oil mists during mechanical action or at elevated temperatures which may be irritating to the respiratory tract. Excessive inhalation of oil mist may affect respiratory system. Causes skin and eye irritation. Swallowing may cause gastrointestinal irritation.
Routes of exposure	Eye contact. Inhalation. Skin contact.
Chronic toxicity	Degreasing. Prolonged or frequent contact may cause redness, itching and eczema/chaps.

Sensitization	The product contains a small amount of sensitizing substance which may provoke an allergic reaction among sensitive individuals.
Carcinogenicity	No carcinogenicity data available for this product.
Mutagenicity	No test data available for the product.
Reproductive Toxicity	No test data available for the product.
Epidemiology	No epidemiological data is available for this product.
Local effects	Irritating to eyes and skin. May cause redness and pain.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Biobase
--------------------	---------

